



Product Service

CERTIFICATE

No. Z2 017297 0529 Rev. 00

Holder of Certificate:



SEILSPIELGERÄTE

Huck Seiltechnik GmbH
Netz- und Seilspielgeräte

Dillerberg 3
35614 Aßlar-Berghausen
GERMANY

Certification Mark:



Product:

swing seats

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713383310-01

Valid until: 2030-11-25

Date, 2025-11-28

(Jens Biesenack)

CERTIFICATE

No. Z2 017297 0529 Rev. 00

Model(s):

- Original Huck Wabennest Art.-Nr.: 4550
- Original Huck Vogelnest Sombrero 1400 mm Art.-Nr.: 4649-140
- Original Huck Vogelnest Art.-Nr.: 4650
- Original Huck Vogelnest Einpunkt Art.-Nr.: 4650E
- Original Huck Vogelnest Kids Midi Art.-Nr.: 4650-1
- Original Huck Mini Vogelnest Art.-Nr.: 4650-85
- Original Huck Mini Vogelnest Art.-Nr.: 4650-85M

Parameters:

The group swing seats consist of a round steel frame covered with shock-absorbing material.

The shock absorption is additionally reinforced at the front ends in the direction of swing. The seat surface consists of an HDPE plastic link mat, which is attached to the inner ring at the sides.

Material

Cushioning: Neopolen 32 kg/m³,

Frame: Stahl Ø 1 ¼"

Art.-Nr.:	Ø [mm]	Weight [kg]	Suspension length [mm]
4550	1040	29.0	1900
4649-140	1400	49.4	1900
4650	1300	40.0	1900
4650E	1300	40.0	1900
4650-1	1180	27.0	1900
4650-85	950	29.4	1840
4650-85M	950	29.0	1000

Flooring made of rubber elements with fabric inserts or HDPE plastic links

Area of application: nursery schools

Use with two-point suspension in accordance with DIN EN 1176-2 Type 1 Area of application: public playgrounds Use with two-point suspension in accordance with DIN EN 1176-2 Type 1, also as a single-point swing in accordance with DIN EN 1176-2 Type 3. The attachment points in the swing frame must be sufficiently cushioned in the case of a cantilever version (cantilever swing).



CERTIFICATE

No. Z2 017297 0529 Rev. 00

**Tested
according to:**

DIN EN 1176-1:2024
EN 1176-1:2017/A1:2023
DIN EN 1176-2:2020
EN 1176-2:2017/AC:2019