



Product Service

CERTIFICATE

No. Z2 017297 0534 Rev. 00

Holder of Certificate:



Huck Seiltechnik GmbH
Netz- und Seilspielgeräte

Dillerberg 3
35614 Aßlar-Berghausen
GERMANY

Certification Mark:



Product:

Playground equipment

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.:

713383310-06

Valid until:

2030-11-25

Date,

2025-12-03

(Jens Biesenack)

CERTIFICATE

No. Z2 017297 0534 Rev. 00

Model(s):

Typ: Rope parcour balance equipment
4591-70-K-X, 4591-71-X, 4591-71-1-X,
4591-72-X, 4591-80-X, 4951-X,
4591-81, 4591-81AM, 4591-81BM,
4591-81RM, 4591-81GM

Parameters:

Item no. / Description	L x W x H [m]
4591-70-K-X Slackmaster	3.10 x 3.50 x 2.04
4591-71-X Slackmaster combination 1 double version	4.00 x 4.00 x 1.44
4591-71-1-X Slackmaster combination 1 single version	5.40 x 0.50 x 1.44
4591-72-X Slackmaster combination 2	3.50 x 3.50 x 2.44
4591-80-X Slack Bar	5.30 x 0.10 x 0.35
4951-X Rubber Jumper	8.10 x 1.40 x 0.70
4591-81 Balancing Snake	9.40 x 0.16 x 0.60
4591-81AM Anaconda Maxi	5.45 x 5.50 x 0.60
4591-81BM Blind Snake Midi	4.15 x 4.13 x 0.60
4591-81RM Earthworm Mini	3.16 x 3.67 x 0.60
4591-81GM Green Mamba	3.50 x 2.33 x 0.60

The X stands for the following variants of the posts:

- S - Steel, St37-2, hot-dip galvanised
- PS - Douglas fir incl. hot-dip galvanised post shoe
- R - Black locust, as grown, sapwood-free

Support posts: Steel Ø102, mm
Douglasie fir Ø 160, 180, 200 mm
Robinie Ø 160 – 400 mm

Ropes/nets: Hercules quality
With steel insert, Ø16 mm

**Tested
according to:**

DIN EN 1176-1:2024
EN 1176-1:2017/A1:2023